

PICO51R

Pico-ITX SBC with 7th Gen Intel® Core™ i7/i5/i3 and Celeron® Processor, DisplayPort++, LVDS and 2 GbE LAN

Features

- 7th generation Intel® Core™ i7/i5/i3 and Celeron® processor
- 1 DDR4 SO-DIMM for up to 16GB of memory
- 2 GbE LAN
- M.2 Key E
- M.2 Key B
- Intel® AMT 11 supported



▲ Assembly view




Core System

CPU	7th gen Intel® Core™ i7/i5/i3 and Celeron® processor onboard
System Memory	1 x 260-pin DDR4-2133 SO-DIMM, up to 16GB
Chipset	SoC integrated
BIOS	AMI
SSD	1 x M.2 Key B 2242 (SATA, USB 2.0, optional PCIe x2)
Watchdog Timer	65536 levels, 0 to 65535 sec.
Expansion Interface	1 x M.2 Key E 2230 (PCIe x1, USB 2.0)
Battery Lithium	Lithium 3V/220 mAh
Power Input	2 x 2-pin connector +12V DC-in only AT Auto Power On function supported
Power Requirements	Intel® Core™ i7-7600U @2.8 GHz 8GB DDR4, min. RMS. +12V@3.2A Intel® Core™ i5-7300U @2.6 GHz 8GB DDR4, min. RMS. +12V@2.6A Intel® Core™ i3-7100U @2.4 GHz 8GB DDR4, min. RMS. +12V@2.3A Intel® Celeron® 3965U @2.2 GHz 8GB DDR4 max. RMS. +12V@1.6A
Dimensions	100 x 72 mm
Board Thickness	1.6 mm
Operating Temperature	-20°C to +60°C (-4°F to 140°F)
Humidity	10% to 95% relative humidity, non-condensing

I/O

SATA	Refer to ordering information
Hardware Monitoring	Detect CPU/system temperature, voltage and fan speed
Ethernet	1 x 10/100/1000 Mbps Ethernet with Intel® I219-LM; supports Wake-on-LAN, PXE Boot ROM 1 x 10/100/1000 Mbps Ethernet with Intel® I210-AT; supports Wake-on-LAN, PXE Boot ROM
Audio	Refer to ordering information
USB	2 x USB 2.0 2 x USB 3.0
Serial	2 x RS-232/422/485
TPM	N/A
SMBus	Yes; compatible with I²C
Digital I/O	4-channel in/out programmable



▲ Side view



▲ Rear view

Display

Chipset	Intel® HD Graphics
Memory Size	Share system memory
Display Interface	1 x DisplayPort++ 1 x LVDS; 18/24-bit single/dual channel

Packing List

Accessories

594H3160400E	Power cable, L=100 mm
--------------	-----------------------

Ordering Information

Standard

PICO51RPGG-i7-7600U (P/N: E38H51R100)	Pico-ITX SBC with Intel® Core™ i7-7600U, DisplayPort, LVDS and 2 GbE LAN
PICO51RPGG-CELERON-3965U (P/N: E38H51R101)	Pico-ITX SBC with Intel® Core™ Celeron-3965U, DisplayPort, LVDS and 2 GbE LAN
PICO51RPGG-i5-7300U (P/N: E38H51R102)	Pico-ITX SBC with Intel® Core™ i5-7300U, DisplayPort, LVDS and 2 GbE LAN
PICO51RPGG-i3-7100U (P/N: E38H51R103)	Pico-ITX SBC with Intel® Core™ i3-7100U, DisplayPort, LVDS and 2 GbE LAN

Optional

PICO51RPGG-i7-7600U W/FAN (P/N: E38H51R104)	Pico-ITX SBC with Intel® Core™ i7-7600U, DisplayPort, LVDS, 2 GbE LAN and cooler
PICO51RPGG-CELERON-3965U W/FAN (P/N: E38H51R105)	Pico-ITX SBC with Intel® Core™ Celeron-3965U, DisplayPort, LVDS, 2 GbE LAN and cooler
PICO51RPGG-i5-7300U W/FAN (P/N: E38H51R106)	Pico-ITX SBC with Intel® Core™ i5-7300U, DisplayPort, LVDS, 2 GbE LAN and cooler
PICO51RPGG-i3-7100U W/FAN (P/N: E38H51R107)	Pico-ITX SBC with Intel® Core™ i3-7100U, DisplayPort, LVDS, 2 GbE LAN and cooler
7128H51R000E	Heatspreader
594H3180400E	DC power cable for adapter, L=180 mm
50966124050E	Adapter 12V 60W FSP060-DHAN3 with screw
59380880250E	COM port cable DB9-9x1P, P=125 mm, L=250 mm
594H51R2810E	USB cable 2 x 5P-cut P9 P2.0/2 x USB-4P, L=180 mm
594H3186800E	Buzzer cable 9 x 5.5 mm 2-pin, L=40mm